Table of contents

- 1 Introduction
- Definition and Purpose
- Basic Limitations of the Conventional Approach
- Spread Spectrum Principles
- Organization of the Book
- 2 Random and Pseudorandom Signal Generation
- Purpose
- Pseudorandom Sequences
- Maximal Length Linear Shift Register Sequences
- Randomness Properties of MLSR Sequences
- Conclusion
- Generating Pseudorandom Signals (Pseudonoise) from Pseudorandom Sequences
- First- and Second-Order Statistics of Demodulator Output in Multiple Access Interference
- Statistics for QPSK Modulation by Pseudorandom Sequences
- Examples
- Bound for Bandlimited Spectrum
- Error Probability for BPSK or QPSK with Constant Signals in Additive Gaussian Noise and Interference
- Appendix 2A Optimum Receiver Filter for Bandlimited Spectrum
- 3 Synchronization of Pseudorandom Signals
- Purpose
- Acquisition of Pseudorandom Signal Timing
- Hypothesis Testing for BPSK Spreading
- Hypothesis Testing for QPSK Spreading
- Effect of Frequency Error
- Additional Degradation When N is Much Less Than One Period
- Detection and False Alarm Probabilities
- Fixed Signals in Gaussian Noise (L=1). Fixed Signals in Gaussian Noise with Postdetection Integration (L> 1). Rayleigh Fading Signals (L> /=1). The Search Procedure and Acquisition Time
- Single-Pass Serial Search (Simplified). Single-Pass Serial Search (Complete). Multiple Dwell Serial Search
- Time Tracking of Pseudorandom Signals
- Early-Late Gate Measurement Statistics
- Time Tracking Loop
- Carrier Synchronization
- Appendix 3A Likelihood Functions and Probability Expressions
- Bayes and Neyman-Pearson Hypothesis Testing
- Coherent Reception in Additive White Gaussian Noise
- Noncoherent Reception in AWGN for Unfaded Signals
- Noncoherent Reception of Multiple Independent Observations of Unfaded Signals in AWGN

- Noncoherent Reception of Rayleigh-Faded Signals in AWGN
- 4 Modulation and Demodulation of Spread Spectrum Signals in Multipath and Multiple Access Interference
- Purpose
- Chernoff and Battacharyya Bounds
- Bounds for Gaussian Noise Channel
- Chernoff Bound for Time-Synchronous Multiple Access Interference with BPSK Spreading
- Chernoff Bound for Time-Synchronous Multiple Access Interference with QPSK Spreading
- Improving the Chernoff Bound by a Factor of
- 2 Multipath Propagation: Signal Structure and Exploitation
- Pilot-Aided Coherent Multipath Demodulation
- Chernoff Bounds on Error Probability for Coherent Demodulation with Known Path Parameters
- Rayleigh and Rician Fading Multipath Components
- Noncoherent Reception
- Quasi-optimum Noncoherent Multipath Reception for M-ary Orthogonal Modulation
- Performance Bounds
- Search Performance for Noncoherent Orthogonal M-ary Demodulators
- Power Measurement and Control for Noncoherent Orthogonal M-ary Demodulators
- Power Control Loop Performance
- Power Control Implications
- Appendix 4A Chernoff Bound with Imperfect Parameter Estimates
- 5 Coding and Interleaving
- Purpose
- Interleaving to Achieve Diversity
- Forward Error Control Coding Another Means to Exploit Redundancy
- Convolutional Code Structure
- Maximum Likelihood Decoder Viterbi Algorithm
- Generalization of the Preceding Example
- Convolutional Code Performance Evaluation
- Error Probability for Tailed-off Block
- Bit Error Probability
- Generalizations of Error Probability Computation
- Catastrophic Codes
- Generalization to Arbitrary Memoryless Channels Coherent and Noncoherent
- Error Bounds for Binary-Input, Output-Symmetric Channels with Integer Metrics
- A Near-Optimal Class of Codes for Coherent Spread Spectrum Multiple Access
- Implementation
- Decoder Implementation

- Generating Function and Performance
- Performance Comparison and Applicability
- Orthogonal Convolutional Codes for Noncoherent Demodulation of **Rayleigh Fading Signals**
- Implementation
- Performance for L-Path Rayleigh Fading
- Conclusions and Caveats
 Appendix 5A Improved Bo